



INVACARE® TOP END® SPORT WHEELCHAIR PRODUCT COMPARISON



Yes, you can.®

Features	Invacare® Top End® Pro™-2 All Sport Wheelchair	Invacare® Top End® Pro™ Basketball/Invacare® Top End® Pro™ Tennis Wheelchairs	Invacare® Top End® Schulte 7000 Basketball Wheelchair/Invacare® Top End® T5 Tennis Wheelchair
Frame Material	6061 T6 aluminum	6061 T6 aluminum	7005 heat treated aluminum
US Price	\$1995.00	\$2395.00	\$2695.00
Seat Width	14", 16", or 18"	12"-20"	14"-20"
Seat Depth	13"-17" adjustable	12"-18"	14"-18"
Front Seat Height Adjustment	18"-20" (½" increments)	Tall: 19"-21" (½" increments) Short: 17"-19"	Not adjustable Fixed height: 14.5"-21"
Rear Seat Height Adjustment	15"-20" (¾" increments)	Tall: 15"-21" (¼" increments) Short: 13"-19"	Not adjustable Fixed height: 14.5"-21"
Footrest Type	Clamp-on tubular double hoop (Adjustable height)	Platform with toe stops Velcro® strap, adjustable forward/backward Up/down and angle	Tubular standard. Adjustable angle (optional) Platform with toe stop (optional)
Frame Construction	Modular: Welded base with seat frame	Modular: Welded base with seat frame	Completely welded (base & seat)
Wheelbase	18" only	15", 17" or 19"	15", 16", 17", 18", 19" or custom
Wing Style(s)	Bumper only (no wing)	4 bend	4 bend, round or bumper
Axle Position-Center of Gravity (COG)	2.5" – 5" (½" increments)	Adjustable: 3.5"-6"	Fixed: 3", 3.5", 4", 4.5", 5", 5.5", 6" or optional COG adjustment
Anti-tip	Single swivel removable telescoping (quick release) adjustable height anti-tip	Single fixed, welded, swivel adjustable height anti-tip Optional: Double anti-tip	Single fixed, welded, swivel adjustable height anti-tip Optional: Double anti-tip
Caster Wheels	72 mm front casters 72 mm - anti-tip	72 mm front casters 59 mm - anti-tip	72 mm front casters 59 mm - anti-tip
Camber	15°	15°, 18°, 20°	15°, 18°, 20°
Rear Wheel Size	25"	24", 25" or 26"	24", 25", 26" or 700C
Wheels	Sun® High Performance	Sun® High Performance	Sun® High Performance
Optional Wheels	No optional wheels	Spinergy® SLX, Sun® Equalizer®	Spinergy® SLX, Sun® Equalizer®
Axles	Quick release	Quick release	Quick release Optional: Titanium
Tires	Primo	Primo Optional: Kenda®	Primo Optional: Kenda®
Pushrim	Aluminum Standard mount 12 tab option	Aluminum Standard or close, no charge Optional cut tab or 12 tab	Aluminum Standard or close, no charge Optional cut tab or 12 tab
Back Style	Fixed, angle adjustable	Fixed or optional folding	Fixed
Back Height	Adjustable: 11"-14"	Adjustable: 9"-11", 11"-14", 14"-18"	Adjustable: 9"-11", 11"-14", 14"-18"
Back Upholstery	Adjustable tension - standard	Adjustable tension - standard	Adjustable tension - standard
Seat Upholstery	Screw on Adjustable depth 13"-17"	Screw on	Adjustable tension or optional solid seat
Side Guard Options	Bolt-on fixed aluminum (specific to Pro-2 Wheelchair)	Clamp on fixed aluminum	Welded, fixed aluminum or carbon
Custom Options	None	None	Heavy duty, double amputee, extra frame depth, tapered seat width, caster center to center, wing style CAD drawings
Overall Weight	23 lb.	23 lb.	21 lb.
Color	14" White, 16" Red, 18" Blue	Customer choice	Customer choice
Assembly	Not factory assembled	Factory assembled	Factory assembled
Weight Capacity	250 lb.	250 lb.	250 lb.

Invacare Corporation www.invacare.com **USA** One Invacare Way, Elyria, Ohio, 44035-4190. (800) 333-6900. **Canada** 570 Matheson Blvd. E., Unit 8, Mississauga, Ontario, L4Z 4G4 Canada. (800) 668-5324. **Top End** www.topendwheelchair.com. 4501 63rd Circle North, Pinellas Park, Florida, 33781-5914. (727) 522-8677. (800) 532-8677. Fax: (727) 522-1007. ©2013 Invacare Corporation. All rights reserved. Trademarks are identified by the symbols ™ and ®. All trademarks are owned by or licensed to Invacare Corporation unless otherwise noted. Velcro is a registered trademark of Velcro Industries B.V. Spinergy is a registered trademark of Spinergy Inc. Sun and Equalizer are a registered trademark of Sun Components. Kenda is a registered trademark of Kenda Rubber Industrial Co., Ltd. Specifications are subject to change without notification. Form No. 13-665 131121